

EVERSKY™



Tender specification

always the best climate

- **EVERSKY™, decentralized self-regulating heat recovery unit, for room-by-room applications, high efficiency (90%).**
- MODBUS, BACNET or WEB **communicating.**
- Self-supporting structure, **external RAL9010 double skin envelope insulated with 25mm M0 high density mineral wool (60 kg/m³).**
- Fitted with a **EUROVENT-certified aluminium counterflow heat exchanger**, F7 (fresh air) and M5 (extracted air) filters mounted on a sealed slide (optional double filtration on fresh air for F7+M5/F9), 100% motorised bypass for **free-cooling** and **night-cooling**, 4 integrated sensors.
- Available in 4 versions (FIRST, SMART, PREMIUM, INFINITE), the **EVERSKY™** central unit can integrate an electric **preheater** as well as an electric or water **heating coil.**
- **Patented removable panels** for numerous airflow configurations.
- Quick and easy full visible or recess under false ceiling mounting with **patented support frame.**
- **Patented On/off internal isolation guillotine dampers** in case of unit switch off.
- **Patented hinges** opening from below.
- **Acoustic data** available on our **SOFTWAIR™** selection tool and approved by the Peutz laboratory in test **N°A 4400-2E-RA-001.**
- Freewheeling fans and low-consumption EC fans.
- Lockable mains power cut-off switch LCD control in "**EASY™**" **control box.**
- **Dual seal round spigots** to guarantee airtightness of networks (ATEC CSTB n° 13-224-V2).
- **Fire safety** function (except SEASON) to control supplied and extracted air fans.
- Integrated condensate drain tray inclined with a 2% slope for easy installation.
- 100% **PLUG&PLAY** range.