

NÉOTIME™



Tender specification

always the best climate

- **NEOTIME™**, extra-flat self-regulated double flow recovery energy unit for false ceiling installation, **high efficiency >90%**.
- **EUROVENT N°21.03.72** (L1/D2/T3/TB3/F9), **VDI 6022** and **VDI 3803** certified range, **ErP2018** compliant.
- **Communicating** in MODBUS, BACNET or WEB.
- Self-supporting structure, **double-skin RAL9007 exterior**, insulated with **25mm M0 high-density mineral wool** (60 kg/m³).
- Fitted with a **EUROVENT-certified aluminium counterflow heat exchanger**, F7 ePM1 55% (fresh air) and M5 ePM10 50% (extracted air) filters mounted on a sealed slide, 100% motorised bypass for free-cooling and night-cooling (except SEASON), **4 integrated sensors**.
- Available in 5 versions (SEASON, FIRST, SMART, PREMIUM, INFINITE), the **NEOTIME™** unit can integrate an electric **preheater** as well as an electric or a water changeover **heating coil**.
- Very low consumption **EC motorised fans**.
- Lockable mains power cut-off switch and **LCD remote control** (optional) except for the SEASON version, which is fitted with 2 potentiometers.
- **Dual seal round spigots** to guarantee airtightness of networks (ATEC CSTB n° 13-224-V2).
- **Fire safety** function (except SEASON) to control supplied and extracted air fans.
- Integrated condensate drain tray inclined with a 2% slope for easy installation.
- 100% **PLUG&PLAY** range.